

Model: **GN2040S9A**

(GOOSENECK SPREAD AXLE AIR-RIDE)



- | | |
|---------------------------|---|
| Est. Tare Wt. | - 9700lbs (±3%) |
| Mfg. Since | - 1990 |
| Features | - Pratt's EZ-GLIDE Friction Free Slider
- Main Rails T-1 (yield 130,000-150,000 psi) Steel |
| Equipped to Handle | - (1) 20FT Container, (1) 40FT High-Cube Container, (2) Empty 20FT Containers, (1) 45 or 48FT Container |
| *Options | - Gooseneck style 20/40 is also available in Tri- Axle Configuration
- Call for any other options |

For pricing & ordering information please feel free to contact us at:



5000 NE Columbia Blvd., Portland, OR 97218
866-600-6645
www.wwtrailers.us

Model: GN2040S9A specifications

Equipped to Handle: (1) 20FT, (1) 40FT, (2) EMPTY 20FT's, (1) 45FT(W/26" OVERSLUNG) and (1) 48FT CONTAINER (W/44" OVERHANG)

DIMENSIONS:

• NOMINAL LENGTH:	45'
• NOMINAL WIDTH:	96"
• KING PIN LOCATION:	36"
• FIFTH WHEEL HEIGHT:	46 1/2"
• REAR DECK HEIGHT:	47"
• AXLE SPREAD:	109"
• TARE WEIGHT:	9,700 LBS (+/- 3%)
• GROSS VEHICLE WEIGHT RATING:	67,000 LBS
• FRAME RATING:	73,000 LBS

GENERAL SPECIFICATIONS:

A. MATERIAL:	Main Rails are of ASTM A514 (140,000 psi); all others are of ASTM A572 Grade 50
B. MAIN RAILS:	Fabricated Continuous I-Beam with T1 top and bottom flanges.
C. CROSSMEMBERS:	Fabricated I-Beam Construction
D. KING PIN:	5/16" pick up plate with 2" diameter double spool king pin.
E. LANDING GEAR:	Two-Speed gears, 19" Travel w/cushion foot.
F. SLIDER:	Pratt's Friction-Free Design.
G. TWISTLOCKS:	Pratt Retractable, Non-Retractable and Flip-up type twistlocks.
H. SUSPENSION:	Tandem Hendrickson HT250US Air-ride 109" Spread, Underslung Configuration.
I. AXLES:	71 1/2" Track w/medium cams, 5" Round, 22,500 lbs each rated.
J. HUB&DRUMS:	Cast steel hub and drum assembly, 10 spoke Hub-Piloted.
K. BRAKES:	16 1/2" x 7" quick-change brakes with non-asbestos lining.
L. RIMS:	8.25 x 22.5 10-hole tubeless type.
M. TIRES:	255/70R22.5 Low Pro Radials, 16 ply.
N. BRAKE SYSTEM:	Valve system for service and emergency brakes. 2S/1M ABS system.
O. ELECTRICAL:	12 VOLT w/modular wiring and plug type connectors and 7-way pin electrical plug for ABS system. Sealed wire Harnesses. Sealed grommets and lights.
P. PAINT:	Enamel based primer and enamel based finishing top coat.
Q. MISC:	Conspicuity Striping, Reflectors, Rubber Bumpers, 24x30 Pratt Mud Flaps.

For pricing & ordering information please feel free to contact us at:



5000 NE Columbia Blvd., Portland, OR 97218
866-600-6645
www.wwtrailers.us