

# Model: **GN2040EZ**

(GOOSENECK TRI-AXLE)



- Est. Tare Wt.** - 10,400 lbs ( $\pm 3\%$ )
- Mfg. Since** - 1990
- Features**
- Pratt's EZ-GLIDE Friction Free Slider
  - Main Rails T-1 (yield 130,000-150,000 psi) Steel
- Equipped to Handle**
- (1) 20FT Container, (1) 40FT High-Cube Container, (2) Empty 20FT Containers for repositioning
- \*Options**
- Gooseneck style 20/40 is also offered in Spring, Spread-Axle or Air-Ride Tri-Axle Configuration
  - Call for any other options

For pricing & ordering information please feel free to contact us at:



5000 NE Columbia Blvd., Portland, OR 97218  
866-600-6645  
[www.wwtrailers.us](http://www.wwtrailers.us)

*Advanced Design Intermodal Equipment*

## Model: GN2040EZ specifications

Equipped to Handle: (1) 20FT ISO CONTAINER, (1) 40FT HIGH-CUBE ISO CONTAINER OR  
(2) EMPTY 20FT ISO CONTAINERS

### DIMENSIONS:

• NOMINAL LENGTH:	41'
• NOMINAL WIDTH:	96"
• KING PIN LOCATION:	16"
• FIFTH WHEEL HEIGHT:	46.5"
• REAR DECK HEIGHT:	48"
• AXLE SPREAD:	122" (Tri-axle)
• TARE WEIGHT:	10,400 LBS (+/- 3%)
• GROSS VEHICLE WEIGHT RATING:	67,000 LBS
• FRAME RATING:	73,000 LBS

### GENERAL SPECIFICATIONS:

A. MATERIAL:	Main Rails are of ASTM A514 (130,000 psi); all others are of ASTM A572 Grade 50
B. MAIN RAILS:	Fabricated Continuous I-Beam with T1 top and bottom flanges.
C. CROSSMEMBERS:	Fabricated I-Beam Construction
D. KING PIN:	5/16" pick up plate with 2" diameter double spool king pin.
E. LANDING GEAR:	Two-Speed gears, 19" Travel w/cushion foot.
F. SLIDER:	Pratt's Friction-Free Design.
G. TWISTLOCKS:	Pratt Retractable, Non-Retractable and Flip-up type twistlocks.
H. SUSPENSION:	Underslung triaxle 61" spread w/undermount fabricated hangers.
I. AXLES:	71 1/2" Track w/medium cams, 5" Round, 22,500 lbs each rated.
J. HUB&DRUMS:	Cast steel hub and drum assembly, 10 spoke Hub-Piloted.
K. BRAKES:	16 1/2" x 7" quick-change brakes with non-asbestos lining.
L. RIMS:	8.25 x 22.5 10-hole tubeless type.
M. TIRES:	255/70R22.5 Low Pro Radials, 16 ply.
N. BRAKE SYSTEM:	Valve system for service and emergency brakes. 2S/1M ABS system.
O. ELECTRICAL:	12 VOLT w/modular wiring and plug type connectors and 7-way pin electrical plug for ABS system. Sealed wire Harnesses. Sealed grommets and lights.
P. PAINT:	Enamel based primer and enamel based finishing top coat.
Q. MISC:	Conspicuity Striping, Reflectors, Rubber Bumpers, 24x30 Pratt Mud Flaps.

**For pricing & ordering information please feel free to contact us at:**



5000 NE Columbia Blvd., Portland, OR 97218  
866-600-6645  
[www.wwtrailers.us](http://www.wwtrailers.us)