

## Model: GN4856

(The Lightest and More Versatile Four-axle Slider For The Northwest)



- Est. Tare Wt.** - 12,130 lbs (±3%)
- Mfg. Since** - 1985
- Features**
- Pratt's EZ-GLIDE Friction Free Slider
  - Main Rails T-1 (yield 130,000-150,000 psi) Steel
- Equipped to Handle** - (1) Overweight 40FT, (1) 45FT or 48FT Container.
- \*Options**
- Model GN 45/53 available in 4 axle configuration for operation in OREGON
  - Call for any other options

For pricing & ordering information please feel free to contact us at:



5000 NE Columbia Blvd., Portland, OR 97218  
866-600-6645  
[www.wwtrailers.us](http://www.wwtrailers.us)

*Advanced Design Intermodal Equipment*

## Model: GN48/56 specifications

**Equipped to Handle:** (1) 40FT, (1) 45FT or (1) 48FT ISO CONTAINERS

### DIMENSIONS:

- NOMINAL LENGTH: 56'
- NOMINAL WIDTH: 96"
- KING PIN LOCATION: 18"
- FIFTH WHEEL HEIGHT: 46"
- REAR DECK HEIGHT: 48"
- AXLE SPREAD: 122" (Tri-axle)
- TARE WEIGHT: 12,130 LBS (+/- 3%)
- GROSS VEHICLE WEIGHT RATING: 87,500 LBS
- FRAME RATING: 95,000 LBS

### GENERAL SPECIFICATIONS:

- A. MATERIAL: Main Rails are of ASTM A514 (140,000 psi); all others are of ASTM A572 Grade 50
- B. MAIN RAILS: Fabricated Continuous I-Beam with T1 top and bottom flanges.
- C. CROSSMEMBERS: Fabricated I-Beam Construction
- D. KING PIN: 5/16" pick up plate with 2" diameter double spool king pin.
- E. LANDING GEAR: Two-Speed gears, 19" Travel w/cushion foot.
- F. SLIDER: Pratt's Friction-Free Design.
- G. TWISTLOCKS: Pratt Retractable, Non-Retractable and Flip-up type twistlocks.
- H. SUSPENSION: Overslung triaxle 61" spread w/undermount fabricated hangers, Steerable Lift Axle with Single Tires
- I. AXLES: 71 1/2" Track w/medium cams, 5" Round, 22,500 lbs each rated.
- J. HUB&DRUMS: Cast steel hub and drum assembly, 10 spoke Hub-Piloted.
- K. BRAKES: 16 1/2" x 7" quick-change brakes with non-asbestos lining.
- L. RIMS: 8.25 x 22.5 10-hole tubeless type.
- M. TIRES: 255/70R22.5 Low Pro Radials, 16 ply.
- N. BRAKE SYSTEM: Valve system for service and emergency brakes. 2S/1M ABS system.
- O. ELECTRICAL: 12 VOLT w/modular wiring and plug type connectors and 7-way pin electrical plug for ABS system. Sealed wire Harnesses. Sealed grommets and lights.
- P. PAINT: Enamel based primer and enamel based finishing top coat.
- Q. MISC: Conspicuity Striping, Reflectors, Rubber Bumpers, 24x30 Pratt Mud Flaps.

**For pricing & ordering information please feel free to contact us at:**



5000 NE Columbia Blvd., Portland, OR 97218  
866-600-6645  
[www.wwtrailers.us](http://www.wwtrailers.us)

*Advanced Design Intermodal Equipment*